



tecnologie per l'efficienza energetica

**479,00 € /cad**  
(IVA E TRASPORTO INCLUSI)



<b>Solar street light 15w</b>		<b>Model: 15WC</b>
Main Lamps material	Aluminium Alloy	
Solar panel	Max Power	18V43W
Battery	li-ion battery	3.7V 192WH
	LiFePO4 battery	3.2V 179WH
LED	Led chip brand	Bridgelux from USA with high brightness
	Lumen(LM)	1500-1650LM
	CCT (k)	6000-7000k
	Life Time	50000 hours
Camera	Pixel	1,100,000 pixel
	Video Compression	Adopt H.264 Main Profile and Baseline profile compression algorithm, Image is more clear, less code flow, be easy to network transmission, and storage space save
	Network function	1,Support the double stream monitor at the same time; 2,Support mobile phone to see; 3,Support 6 users monitor the IP Camera at the same time; 4,Build-in WEB SERVER, Support IE browse and parameter setting, use one port for data transmitting, making it easy for users to network Settings; 5,Support 802.11b/g/n agreement,can be built-in wifi module, Flexible forming wireless monitoring environment; 6,Supports four regional Motion Detection and alarm linkage call presets;
	storage	32G TF card
	Interface	WIFI
Lighting Viewing Angle	140°×70°	
Working TEMP( °C )	-20°~+60°	
Working Mode	Sensing mode	
Charge time(by sun):	8-10hours (with enough strong shine)	
Discharge time	10-12 hours per night 3-5rainy days	
Certificate	CE/ROHS/IP66	
Packing	Product size	882*315*206 mm
	Packing size	Box 1: 990*440*180mm (lamp body) Box 2 : 350*290*220mm(Supportor+Accessories )
	Net weight	8.5 kg
	Gross weight	10.5 kg
	Packing way	1sets/2carton
Packs Containers	20ft container	290pcs